A Measured Energy Transformation Application (META) For Long Beach Harbor, Site 2 Using A Statistical Relationship

James P. McKinney and William D. Corson
U.S. Army Corps of Engineers Engineering Research & Development Center
Vicksburg, MS, 39180

August 28, 2003

This discussion compares prototype and computed spectral results for gages located at Long Beach Harbor, CA. Comparisons are made by examining the differences in the prototype and computed harbor total energy, E_t, very long period energy between 200 and 30 seconds, E_{200-30}, and energy spectrums. Spectral analysis allows the energy of the total wave record to be broken down into discrete frequency bands. Spectral results from an incident gage, LB8, located at Queens Gate and Long Beach Site 2, LB2, were used to calculate an energy transfer spectrum for LB2.

Wave records were collected every 4 hours using subsurface pressure sensors. The sample rate for these sensors was 0.5 H_z and the burst length was 8096 seconds.

The analysis utilized the Welch, [1], spectral analysis method with 50% overlapping segments. Since the raw time series were obtained using sub-surface systems, a depth determined high frequency cutoff was applied. The averaged co-and quad-spectra from each analyzed record were used to calculate E_t, E_{200-30}, and energy spectrums.

To provide a direct comparison of incident and transferred energy, a transfer coefficient spectrum, S_x, was calculated by dividing the transferred energy at each frequency by the corresponding incident energy, eqn.1.

$$E_{xf} = \frac{E_{tf}}{E_{if}} \tag{1}$$

where E_{tf} is the energy per frequency transferred at LB2 and E_{if} is the incident energy per frequency from LB8. For this simple analysis, concurrent records when the LB8 $E_{200-30} >$ 5.0 cm^2 were selected to compute S_x.

Plots of the yearly S_x spectrums for 1998 - 2002 are provided. See figures 1 thru 5.

An estimated energy spectrum, S_{est} at LB2 was calculated for each incident spectrum, S_i, using equation, eqn.2.

Report Documentation Page

Form Approved
OMB No. 0704-0188

1. REPORT DATE	2. REPORT TYPE	3. DATES COVERED
28 AUG 2003		**00-08-2003 to 00-08-2003**

4. TITLE AND SUBTITLE	5a. CONTRACT NUMBER
A Measured Energy Transformation Application (META) for Long Beach Harbor, Site 2 Using a Statistical Relationship	5b. GRANT NUMBER
	5c. PROGRAM ELEMENT NUMBER
6. AUTHOR(S)	5d. PROJECT NUMBER
	5e. TASK NUMBER
	5f. WORK UNIT NUMBER
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) **Army Engineer Research and Development Center,Waterways Experiment Station,3909 Halls Ferry Road,Vicksburg,MS,39180**	8. PERFORMING ORGANIZATION REPORT NUMBER
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)	10. SPONSOR/MONITOR'S ACRONYM(S)
	11. SPONSOR/MONITOR'S REPORT NUMBER(S)

12. DISTRIBUTION/AVAILABILITY STATEMENT
Approved for public release; distribution unlimited

13. SUPPLEMENTARY NOTES

14. ABSTRACT

15. SUBJECT TERMS

16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON
a. REPORT	b. ABSTRACT	c. THIS PAGE			
unclassified	**unclassified**	**unclassified**		**9**	

Standard Form 298 (Rev. 8-98)
Prescribed by ANSI Std Z39-18

$$S_{est} = S_x S_i \tag{2}$$

Figure 6 shows plots of prototype and estimated energy spectrums for LB2 for February 14 & 15, 2001. It is interesting that the part of the spectrums below 0.05 H_z are similar. E_{200-30} and E_t where calculated from the S_{est} for each record. Figure 7 show simultaneous plots of E_t and E_{200-30} for the prototype and estimated results. The scatter plots at the bottom of the page contain the same information. The overall average % error for E_{200-30} was 21.97% and was 45.79% for E_t.

For more information, contact: James P. McKinney or William D. Corson, CEERD-HC-SO.

References

[1] P. D. Welch, "The Use of Fast Fourier Transform for the Estimation of Power Spectrum: A Method Based on Time Averaging Over Short, Modified Periodogams," *IEEE Transactions on Audio and Electroacoustics*, June 1967.



Figure 1: Average transfer spectrum, S_x, when incident E_{200-30}>5.0 cm^2 for 1998.



Figure 2: Average transfer spectrum, S_x, when incident E_{200-30}>5.0 cm^2 for 1999.



Figure 3: Average transfer spectrum, S_x, when incident E_{200-30}>5.0 cm^2 for 2000.



Figure 4: Average transfer spectrum, S_x, when incident E_{200-30}>5.0 cm^2 for 2001.



Figure 5: Average transfer spectrum, S_x, when incident E_{200-30}>5.0 cm^2 for 2002.



Figure 6: Prototype and estimated energy spectrums for May 14 & 15, 2001. Long period energies are similar.



Figure 7: Prototype and estimated total energy, E_t, and very long period energy, E_{200-30}.